



TCL LED SERIES Installation Instructions




Remove this sheet prior to final installation

Wall Mount Install Instructions

• Remove the back panel of the unit by unscrewing the two retaining screws on the bottom of the unit.



• Mount the back panel to the appropriate building face with four (4) fasteners. (Not Supplied)




• Lift the cabinet on the top edge of the back panel and shift forward, make wire connections according to the instructions, then replace the back and the two retaining screws removed in step one.



Note: Do not overtighten fasteners or distort back panel.


Note: Clear any metal chips from inside sign cabinet, failure to do so may void warranty.

Single/Double Post Mounts




Direct Burial

Base Plate



Projection Post


Dual Angle Mount




30° Angle

45° Angle

Ceiling/Side Mount





Ceiling Mount



Side Mount

Optional Mounting Hardware Available for Immediate Shipping.
Order it TODAY, Receive it TOMORROW!



TCL Dual Message Wiring Diagram



To Wire Dual Message Signs

- Connect Black Message A primary lead and Red Message B primary lead to opposite switch poles.
- Connect white neutral wire opposite switch pole and to supply circuit.
- Connect ground wire


TCL Single Message Wiring Diagram



To Wire Single Message Signs

- Connect Red Message B primary lead to switch pole.
- Connect white neutral wire opposite switch pole and to supply circuit.
- Connect ground wire

Switches Available for
Immediate Shipping.
Order it TODAY,
Receive it TOMORROW!



Note: Make appropriate wiring connections per local code.

Note: This sign is intended to be installed in accordance with the requirements of Article 600 of the National Electric Code and/or other applicable local codes. This includes proper grounding and bonding of the sign.